

# READ ME FIRST!

## Van Horn Aviation 206B/L Tail Rotor Blades P/N 2062200-501

Congratulations! You are about to install Van Horn Aviation (VHA) composite rotor blades. These blades are designed to be different than the OEM blades, providing more performance and longer service life. Our blades require **SLIGHTLY DIFFERENT** installation procedures and may require **PILOT RE-ACQUAINTANCE**.

FOR BEST RESULTS, DO THE FOLLOWING:

1. Download the appropriate Instructions for Continued Airworthiness (ICA) and Flight Manual Supplement (206L models only) for your model of helicopter from [www.vanhornaviation.com/documents](http://www.vanhornaviation.com/documents).
2. Read and follow the instructions in the ICA.
3. **SUBTRACT** a half (1/2) degree from standard tail rotor rig procedures.
4. **REMOVE ALL** of your existing **COUNTER WEIGHT** washers, weight attachment bolt and nut to relieve right pedal pressure.
5. Brief your pilots that the pedals may feel different. If the blades are rigged correctly, pilots will input **NEUTRAL OR SLIGHT RIGHT** pedal on takeoff.

### WARRANTY INFORMATION

Van Horn Aviation warrants this product to be free from defects in workmanship and materials, under normal use and conditions, for a period of three (3) years from date of manufacture or 1,500 flight hours (whichever comes first). This warranty excludes bearing replacement and damage due to erosion or object strike.

QUESTIONS? Visit [www.vanhornaviation.com](http://www.vanhornaviation.com) or call 1-480-483-4202.

